



Interface:Full detent

CABLE(UT086,RG405,670-086)

3	1	Body	Brass/Gold plated	Gold 0.2 um over Nickel 2um
2	1	Insulator	PTFE	
1	1	Center contact	Brass/Gold plated	Gold 0.5 um over Nickel 2um

Designed by	Checked by	Approved by - date	File name	Date	Scale
			S3-115QQA		
				Edition	Sheet

CHARACTERISTICS

DESCRIPTION:

SMP Type male connector

Electrical data:

Impedance:	50 ohm
Frequency range:	DC to 18 GHz
VSWR:	$\leq 1.35:1$
Insertion loss:	$\leq 0.1X\sqrt{f[\text{GHz}]} \text{ dB}$
Insulation resistance:	$\geq 5000M\Omega$
Test voltage:	500 V rms
Working voltage:	335 V rms
Contact resistance:	
1). Centre contact:	6.0 m Ω
2). Outer conductor:	2.0 m Ω

Environmental data:

Temperature rating:	-65 ° C to +165 ° C
2002/95/EC (RoHS):	Compliant

Mechanical data:

Mating cycles:

- if mating part is full detent:	≥ 100
Center contact captivation:	$\geq 7 \text{ N(axial)}$
Engagement force:	

- full detent:	$\leq 68 \text{ N.}$
Disengagement force:	

- full detent:	$\geq 22 \text{ N.}$
----------------	----------------------

Suitable cables:

UT086,RG405,670-086